MULTI-BEND LED STRIP LIGHT

Model: FA60S28-5M-12V-X (X = COLOR R:Red, B: Blue)

HUEDA LED
www.huedaled.com



BENEFITS

- Angle bendable for custom shape lighting applications
- View Angle 120°
- Double sided 3M Tape backing
- Ultra bright surface - mount LEDs
- Low power consumption and little heat
- No RF interference
- Small Strip width allows to fit within tiny lighting areas
- Long life of LEDs
- Solid-state lighting
- Can be cut to size at marked intervals (Qualified personnel)
- Available in Red & Blue

APPLICATIONS

- Backlit Channel Letters
- Architectural accenting
- Backlighting of glass and acrylic
- Corporate showrooms and exhibition Sign displays
- Optional aluminum mounting channel with clear and diffused lens

SPECIFICATIONS

Roll Size	5 Meters (16.4 Feet)
Max Voltage	12 VDC (regulated/Class 2)
Watt Foot	1.8 (2.5 Amps/Roll)
Light Source	60 pcs/Meter (39.37") 2835 SMD LED
Dimensions	5000(L) x 8.0(W) x 1(H)mm (16.4' x 0.31" x 0.03")
Max Length	5 Meters (16.4 Feet)
View Angle	120°
Brightness	200~220 LM/ft (30.5cm)
Color Temp.	WW: 3100K, W: 4100K, Blue
Lamp Life	>25,000 hours (average life)
IP Rating	IP20 Type A
Mount	Smooth Clean Surface/burrows free
Operating Temperature	-25°C ~ +40°C (-13°F ~ +104°F)

MODEL

FA60S28-5M-12V-X

- **COLOR** (Red, Blue)
- **VOLTAGE** (12V)
- **LENGTH** (5 Meters/16.4 Foot)
- **LED TYPE** (2835 SMD)
- **LED/METER** (60LED/Meter)
- **COVER TYPE** (Type A, no coating)
  A=IP20 **B**=IP62 **C**=IP64
- **FLEX STRIP**







DIAGRAM







LED Flex Strip



OPTIONAL POWER SUPPLIES/ACCESSORIES

MD-012-060VTDHV2 (60W) Dimmable Class 2	MD-012-180VTD52JV2 (180W) Multi tab Dimmable Class 2 Driver	MD-012-300VTD52JV2 (300W) Multi tab Dimmable Class 2 Driver	Wago Block Connectors (#221-413)
			



Copyright © 2022 HUEDA™ LED, A division of LED World Inc.. All Rights Reserved. We are not responsible for errors or omissions. Product and specifications subject to change without notice. Registered trademarks are owned by their respective registers, or licensee(s).